

PLIMAT

Family 19b

Acessórios de encaixe rápido Plast

Products	18
References	165

19.29 Elbow 90°

Material: not defined	Quick coupling	10 references
-----------------------	----------------	---------------

d	A	L	Z	I	Weight (g)	Pack	REF.	3D
16	47	54	13	67	88	45	20402001016	-
20	47	54	13	67	82	45	20402001020	-
25	54	56	17	73	105	30	20402001025	-
32	63	61	18	79	304	20	20402001032	-
40	80	74	23	97	304	10	20402001040	-
50	94	85	28	113	506	12	20402001050	-
63	116	95	29	124	916	-	20402001063	-
75	121	134	48	182	1250	-	20402001075	-
90	146	155	51	208	1890	-	20402001090	-
110	176	176	58	234	3310	-	20402001110	-

Dimension key: d = Ø exterior do tubo (mm), L = Comprimento (mm), I = Profundidade de encaixe (mm)

19.30 Elbow with wall suport

Material: not defined	Quick coupling	2 references
-----------------------	----------------	--------------

d	G	A	L	L1	Z	I	R	Weight (g)	Pack	REF.	3D
20	" 1 / 2	47	18	65	11	29	21	66	50	20402195005	-
25	" 3 / 4	54	20	73	11	31	21	86	40	20402195020	-

Dimension key: d = Ø exterior do tubo (mm), G = Rosca (in), L = Comprimento (mm), L1 = Comprimento (2) (mm), I = Profundidade de encaixe (mm)

19.31 Tee 90°

Material: not defined	Quick coupling	10 references
-----------------------	----------------	---------------

d	A	L	Z	Z1	I	Weight (g)	Pack	REF.	3D
16	47	54	26	13	134	127	30	20402003016	-
20	47	54	26	13	134	115	30	20402003020	-
25	54	56	34	17	146	165	20	20402003025	-

d	A	L	Z	Z1	I	Weight (g)	Pack	REF.	3D
32	63	61	36	18	158	250	12	20402003032	-
40	80	74	46	23	194	441	5	20402003040	-
50	94	85	56	28	226	726	8	20402003050	-
63	116	95	58	29	248	1300	-	20402003063	-
75	121	134	96	48	364	1900	-	20402003075	-
90	146	155	102	51	416	2850	-	20402003090	-
110	176	176	116	58	468	4750	-	20402003110	-

Dimension key: d = Ø exterior do tubo (mm), L = Comprimento (mm), I = Profundidade de encaixe (mm)

19.32 Reducing tee 90°

Material: not defined Quick coupling 6 references

d	d1	A	A1	L	L1	Z	Z1	I	I1	Weight (g)	Pack	REF.	3D
25	20	54	47	56	54	34	21	146	75	160	20	20402004105	-
32	25	63	54	61	56	36	31	158	87	250	12	20402004110	-
40	32	80	63	74	61	46	38	194	99	390	8	20402004115	-
50	32	94	63	85	65	56	36	226	102	600	8	20402004119	-
50	40	94	80	85	74	56	43	226	117	657	8	20402004120	-
63	50	116	94	95	85	58	37	248	122	1160	8	20402004125	-

Dimension key: d = Ø exterior do tubo (mm), d1 = Ø exterior do tubo (2.ª saída) (mm), L = Comprimento (mm), L1 = Comprimento (2) (mm), I = Profundidade de encaixe (mm), I1 = Profundidade de encaixe (2) (mm)

19.33 Female union elbow 90°

Material: not defined Threaded 15 references

d	G	A	L	L1	Z	Z1	I	I1	Weight (g)	Pack	REF.	3D
16	" 1/2	47	54	17	13	26	67	43	69	70	20402002003	-
20	" 1/2	47	54	17	13	26	67	43	65	70	20402002005	-
20	" 3/4	47	54	18	13	27	67	45	64	70	20402002006	-
25	" 1/2	54	56	17	17	31	73	48	80	40	20402002009	-
25	" 3/4	54	56	17	17	31	73	48	84	40	20402002010	-
25	1"	54	56	19	17	29	73	48	84	30	20402002011	-
32	" 3/4	63	61	20	18	38	79	59	148	30	20402002013	-
32	1 "	63	61	20	18	38	79	59	135	30	20402002015	-
40	1 "	80	74	22	23	41	97	63	210	15	20402002019	-
40	1" 1/4	80	74	22	23	41	97	63	217	15	20402002020	-
50	1" 1/2	94	85	22	28	54	113	76	380	18	20402002025	-
63	2 "	116	96	26	29	57	124	83	650	20	20402002030	-
75	2" 1/2	121	134	34	48	51	182	85	880	14	20402002060	-
90	3 "	146	155	37	51	68	208	105	1414	8	20402002065	-
110	4 "	176	176	42	58	82	234	124	2317	4	20402002070	-

Dimension key: d = Ø exterior do tubo (mm), G = Rosca (in), L = Comprimento (mm), L1 = Comprimento (2) (mm), I = Profundidade de encaixe (mm), I1 = Profundidade de encaixe (2) (mm)

19.34 Female union tee 90°

Material: not defined

Threaded

15 references

d	G	A	L	L1	Z	Z1	I	I1	Weight (g)	Pack	REF.	3D
16	" 1/2	47	54	16	26	27	134	43	111	40	20402004003	-
20	" 1/2	47	54	16	26	27	134	43	101	40	20402004005	-
20	" 3/4	47	54	17	26	29	134	46	103	40	20402004006	-
25	" 1/2	54	56	18	34	30	146	48	131	25	20402004009	-
25	" 3/4	54	56	18	34	30	146	48	131	25	20402004010	-
25	1"	54	56	19	34	30	146	49	130	25	20402004011	-
32	" 3/4	63	61	18	36	40	158	58	227	15	20402004014	-
32	1 "	63	61	21	36	37	158	58	196	15	20402004015	-
40	1 "	80	74	21	46	42	194	63	355	8	20402004019	-
40	1" 1/4	80	74	23	46	40	194	63	340	8	20402004020	-
50	1" 1/2	94	85	23	56	53	226	76	569	10	20402004025	-
63	2 "	116	95	27	58	58	248	85	996	11	20402004030	-
75	2" 1/2	121	134	33	96	52	364	85	1500	10	20402004060	-
90	3 "	146	155	37	102	65	416	102	2406	4	20402004065	-
110	4 "	176	176	42	116	82	468	124	3670	2	20402004070	-

Dimension key: d = Ø exterior do tubo (mm), G = Rosca (in), L = Comprimento (mm), L1 = Comprimento (2) (mm), I = Profundidade de encaixe (mm), I1 = Profundidade de encaixe (2) (mm)

19.35 Male union elbow 90°

Material: not defined

Threaded

10 references

d	G	A	L	L1	Z	Z1	I	I1	Weight (g)	Pack	REF.	3D
20	" 1/2	47	54	14	13	32	67	46	56	70	20402085005	-
20	" 3/4	47	54	16	13	27	67	43	53	70	20402085006	-
25	" 1/2	54	56	14	17	38	73	52	77	40	20402085009	-
25	" 3/4	54	56	16	17	36	73	52	76	40	20402085010	-
32	" 3/4	63	61	16	18	45	79	61	128	30	20402085014	-
32	1 "	63	61	19	18	42	79	61	119	30	20402085015	-
40	1 "	80	74	19	23	45	97	64	200	15	20402085019	-
40	1" 1/4	80	74	21	23	46	97	67	212	15	20402085020	-
50	1" 1/2	94	85	21	28	61	113	82	356	18	20402085025	-
63	2 "	116	96	25	29	57	124	82	630	20	20402085030	-

Dimension key: d = Ø exterior do tubo (mm), G = Rosca (in), L = Comprimento (mm), L1 = Comprimento (2) (mm), I = Profundidade de encaixe (mm), I1 = Profundidade de encaixe (2) (mm)

19.36 Male union tee 90°

Material: not defined

Threaded

9 references

d	G	A	L	L1	Z	Z1	I	I1	Weight (g)	Pack	REF.	3D
20	" 1/2	47	54	14	26	32	134	42	92	40	20402086005	-
20	" 3/4	47	54	14	26	32	134	42	90	40	20402086006	-

d	G	A	L	L1	Z	Z1	I	I1	Weight (g)	Pack	REF.	3D
25	" 1/2	54	56	16	26	28	134	44	115	30	20402086009	-
25	" 3/4	54	56	16	34	36	146	51	123	30	20402086010	-
32	" 3/4	63	61	19	36	42	158	61	206	15	20402086014	-
32	1 "	63	61	19	36	42	158	61	200	15	20402086015	-
40	1" 1/4	80	74	21	46	46	194	67	351	9	20402086020	-
50	1" 1/2	94	85	21	56	61	226	82	572	10	20402086025	-
63	2 "	116	95	25	58	57	248	82	1022	12	20402086030	-

Dimension key: d = Ø exterior do tubo (mm), G = Rosca (in), L = Comprimento (mm), L1 = Comprimento (2) (mm), I = Profundidade de encaixe (mm), I1 = Profundidade de encaixe (2) (mm)

19.37 Coupling

Material: not defined Quick coupling 10 references

d	A	L	Z	I	Weight (g)	Pack	REF.	3D
16	47	51	3	105	78	50	20402005016	-
20	47	52.5	3	108	72	50	20402005020	-
25	54	57	3	117	93	40	20402005025	-
32	63	60	4	124	155	25	20402005032	-
40	80	74	6	154	290	13	20402005040	-
50	94	85	8	178	454	15	20402005050	-
63	116	104	4	212	817	15	20402005063	-
75	121	138	5	281	1110	14	20402005075	-
90	146	145	3	293	1580	8	20402005090	-
110	176	174	6	354	2740	4	20402005110	-

Dimension key: d = Ø exterior do tubo (mm), L = Comprimento (mm), I = Profundidade de encaixe (mm)

19.38 Cap

Material: not defined Quick coupling 10 references

d	A	L	I	Weight (g)	Pack	REF.	3D
16	47	52	58	41	125	20402012016	-
20	47	52	58	38	125	20402012020	-
25	54	57	63	55	75	20402012025	-
32	63	61	67	85	50	20402012032	-
40	80	75	83	150	24	20402012040	-
50	94	85	94	240	30	20402012050	-
63	116	92	104	467	34	20402012063	-
75	121	154	164	650	23	20402012075	-
90	146	165	175	910	16	20402012090	-
110	176	180	195	1620	8	20402012110	-

Dimension key: d = Ø exterior do tubo (mm), L = Comprimento (mm), I = Profundidade de encaixe (mm)

19.39 Reduced union

Material: not defined

Quick coupling

14 references

d	d1	A	A1	L	L1	Z	I	Weight (g)	Pack	REF.	3D
20	16	47	47	51	54	3	108	74	45	20402007003	-
25	16	54	47	56	51	5	112	83	45	20402007004	-
25	20	54	47	56	51	5	112	84	45	20402007005	-
32	20	63	47	59	51	5	115	107	30	20402007009	-
32	25	63	54	61	56	5	122	120	30	20402007010	-
40	25	80	54	73	56	4	133	177	18	20402007014	-
40	32	80	63	73	59	6	138	194	18	20402007015	-
50	32	94	63	85	58	5	148	305	22	20402007019	-
50	40	94	80	85	75	3	163	350	20	20402007020	-
63	40	116	80	104	75	10	189	531	20	20402007024	-
63	50	116	94	91	85	6	182	620	20	20402007025	-
75	63	121	116	143	95	7	245	1000	14	20402007030	-
90	75	146	121	151	147	8	306	1360	8	20402007035	-
110	90	176	146	180	160	8	348	3230	5	20402007040	-

Dimension key: d = Ø exterior do tubo (mm), d1 = Ø exterior do tubo (2.ª saída) (mm), L = Comprimento (mm), L1 = Comprimento (2) (mm), I = Profundidade de encaixe (mm)

19.40 Female nipple

Material: not defined

Quick coupling

17 references

d	G	A	L	L1	Z	I	Weight (g)	Pack	REF.	3D
16	" 1/2	47	54	17	5	76	56	90	20402065003	-
16	" 3/4	47	54	17	5	73	56	90	20402065004	-
20	" 1/2	47	54	17	5	76	49	90	20402065005	-
20	" 3/4	47	54	17	4	75	56	90	20402065010	-
25	" 1/2	54	60	17	1	78	64	60	20402065019	-
25	" 3/4	54	56	17	7	80	67	60	20402065020	-
25	1 "	54	56	20	8	84	75	60	20402065022	-
32	" 3/4	63	63	20	4	87	96	35	20402065034	-
32	1 "	63	63	20	4	87	102	35	20402065035	-
32	1" 1/4	63	69	20	5	94	110	35	20402065036	-
40	1 "	80	78	22	3	103	182	22	20402065044	-
40	1" 1/4	80	74	22	9	105	168	22	20402065045	-
50	1" 1/2	94	85	22	8	115	274	27	20402065050	-
63	2 "	116	91	26	9	126	476	30	20402065055	-
75	2" 1/2	121	141	28	9	178	672	20	20402065060	-
90	3 "	146	151	31	8	190	970	12	20402065065	-
110	4 "	176	174	42	5	221	1665	6	20402065070	-

Dimension key: d = Ø exterior do tubo (mm), G = Rosca (in), L = Comprimento (mm), L1 = Comprimento (2) (mm), I = Profundidade de encaixe (mm)

19.41 Male nipple

Material: not defined

Quick coupling

22 references

d	G	A	L	L1	I	Weight (g)	Pack	REF.	3D
16	" 1/2	47	52	15	74	42	90	20402037003	-
16	" 3/4	47	52	15	74	44	90	20402037004	-
20	" 1/2	47	51	15	71	40	90	20402037005	-
20	" 3/4	47	52	16	72	40	90	20402037010	-
25	" 1/2	54	60	15	82	56	60	20402037015	-
25	" 3/4	54	58	15	80	59	60	20402037020	-
25	1 "	54	58	18	83	64	60	20402037025	-
32	" 3/4	63	60	15	83	86	40	20402037030	-
32	1 "	63	60	20	86	87	40	20402037035	-
32	1" 1/4	63	58	19	86	92	40	20402037040	-
40	1 "	80	74	20	102	154	23	20402037042	-
40	1" 1/4	80	74	22	104	147	23	20402037045	-
40	1" 1/2	80	74	20	102	143	22	20402037046	-
50	1" 1/4	96	86	19	112	222	30	20402037049	-
50	1" 1/2	94	86	24	117	231	27	20402037050	-
50	2 "	94	88	25	115	232	25	20402037052	-
63	1" 1/2	116	105	24	138	424	34	20402037053	-
63	2 "	116	105	25	139	427	30	20402037055	-
75	2 "	121	147	28	184	645	20	20402037059	-
75	2" 1/2	121	154	30	195	652	20	20402037060	-
90	3 "	146	160	34	206	932	12	20402037065	-
110	4 "	176	176	43	233	1645	6	20402037070	-

Dimension key: d = Ø exterior do tubo (mm), G = Rosca (in), L = Comprimento (mm), L1 = Comprimento (2) (mm), I = Profundidade de encaixe (mm)

19.42 Reducing elbow 90°

Material: not defined

Quick coupling

3 references

d	d1	A	A1	L	L1	Z	Z1	I	I1	Weight (g)	Pack	REF.	3D
25	16	54	47	59	56	15	18	74	74	98	35	20402002104	-
25	20	54	47	59	56	15	18	74	74	100	35	20402002105	-
32	25	63	54	58	59	22	24	80	83	147	20	20402002110	-

Dimension key: d = Ø exterior do tubo (mm), d1 = Ø exterior do tubo (2.ª saída) (mm), L = Comprimento (mm), L1 = Comprimento (2) (mm), I = Profundidade de encaixe (mm), I1 = Profundidade de encaixe (2) (mm)

19.43 Slip coupling

Material: not defined

Quick coupling

5 references

d	A	I	Weight (g)	Pack	REF.	3D
50	94	178	414	15	20402185050	-
63	116	212	770	17	20402185063	-

d	A	I	Weight (g)	Pack	REF.	3D
75	121	281	1062	14	20402185075	-
90	146	293	1580	8	20402185090	-
110	176	354	2800	-	20402185110	-

Dimension key: d = Ø exterior do tubo (mm), I = Profundidade de encaixe (mm)

19.44 Compression flange

Material: not defined Flanged 5 references

d	A	L	I	B	K	Y	Furos	Weight (g)	Pack	REF.	3D
50	94	100	114	150	55	18	4	1140	10	20402200050	-
63	116	124	138	164	58	18	4	1450	18	20402200063	-
75	121	162	177	183	73	18	4	2027	10	20402200075	-
90	146	167	186	200	80	18	8	2320	8	20402200090	-
110	176	186	210	220	91	18	8	2972	6	20402200110	-

Dimension key: d = Ø exterior do tubo (mm), L = Comprimento (mm), I = Profundidade de encaixe (mm), Furos = N.º de furos (un)

19.45 Tee with double female offtake

Material: not defined Threaded 1 references

d	G	A	L	L1	Z	Z1	I	I1	Weight (g)	Pack	REF.	3D
32	"3/4	63	61	21	41	38	163	59	211	30	20402068014	-

Dimension key: d = Ø exterior do tubo (mm), G = Rosca (in), L = Comprimento (mm), L1 = Comprimento (2) (mm), I = Profundidade de encaixe (mm), I1 = Profundidade de encaixe (2) (mm)

19.26 Double spanner

Material: not defined Quick coupling 1 references

Ø	Weight (g)	Pack	REF.	3D
16-63 mm	-	-	07417781005	-

Dimension key: Ø = Diâmetro