

01.12 Reducción hembra/hembra

PVC-U	Roscar	10 referencias	10 con archivo CAD						
G	G1	I	L	L1	S	Peso (g)	Emb.	REF.	3D
"3/4	" 1/2	33.5	15	13	38	25	B 120	01011007005	sim
1"	" 1/2	36	17	13	46	35	B 80	01011007006	sim
1"	" 3/4	38	17	15	46	40	B 70	01011007007	sim
1" 1/4	" 1/2	40	22	13	53	50	B 80	01011007008	sim
1" 1/4	" 3/4	43	22	15	53	52	B 70	01011007009	sim
1" 1/4	1 "	45	22	17	53	58	B 60	01011007010	sim
1" 1/2	" 1/2	44	23	13	65	86	B 45	01011007011	sim
1" 1/2	" 3/4	47	23	15	65	89	B 45	01011007012	sim
1" 1/2	1 "	49	23	17	65	94	B 40	01011007013	sim
1" 1/2	1" 1/4	55	23	22	65	100	B 30	01011007014	sim

Leyenda de cotas: G = Rosca (in), G1 = Rosca (2.ª saída) (in), I = Profundidade de encaixe (mm), L = Comprimento (mm), L1 = Comprimento (2) (mm)

PDF: /images/pdf/capitulo1/01-12.pdf