

01.13 Short reducer male/female

PVC-U

Threaded

13 references

13 with CAD file

G	G1	I	Z	S	Weight (g)	Pack	REF.	3D
" 1/2	" 1/4	22	8	23	7	A 80	01011080002	sim
" 3/4	" 1/2	28	13	29	12	A 50	01011080004	sim
1 "	" 1/2	28	13	35	20	A 30	01011080006	sim
1 "	" 3/4	28	9	35	14	A 30	01011080007	sim
1" 1/4	" 1/2	31	16	44	29	B 140	01011080008	sim
1" 1/4	" 3/4	31	13	44	33	B 140	01011080009	sim
1" 1/4	1 "	31	10	44	25	B 140	01011080010	sim
1" 1/2	" 3/4	34.5	17	50	43	B 100	01011080012	sim
1" 1/2	1 "	34.5	12	50	44	B 100	01011080013	sim
1" 1/2	1" 1/4	34.5	12	50	29	B 100	01011080014	sim
2 "	1"	38	15	62	74	B 50	01011080016	sim
2 "	1" 1/4	38	13	62	76	B 50	01011080017	sim
2 "	1" 1/2	38	13	62	62	B 50	01011080018	sim

Dimension key: G = Rosca (in), G1 = Rosca (2.ª saída) (in), I = Profundidade de encaixe (mm)

PDF: /images/pdf/capitulo1/01-13.pdf