

01.22 Traversée de paroi en PVC

PVC-U Fileté 9 références 9 avec fichier CAO

G	G1	d	d1	L	L1	Z	I	S	Poids (g)	Cond.	RÉF.	3D
" 1/2	" 1/2	16	14.5	16	33	13	61	25	19	B 150	01011312012	sim
"3/4	"3/4	20	20	19	42	17	74	32	41	B 70	01011312034	sim
1"	1"	25	25	22	45	19	82	40	66	B 40	01011312100	sim
1" 1/4	1" 1/4	32	32	23	49	20	91	50	110	B 25	01011312114	sim
1" 1/2	1" 1/2	37	37	23	49	23	91	60	170	C 60	01011312150	sim
1" 1/2	1" 3/4	37	40	23	49	23	91	60	173	C 60	01011312022	sim
2"	2"	49.5	50	27	52	25	100	69	200	C 40	01011312200	sim
2 " 1/2	2 " 1/2	63	63	30	52	25	103	78	255	C 35	01011312250	sim
3 "	3 "	75	75	33	58	28	112	92	340	C 24	01011312300	sim

Légende des cotes: G = Rosca (in), G1 = Rosca (2.^a saída) (in), d = Ø exterior do tubo (mm), d1 = Ø exterior do tubo (2.^a saída) (mm), L = Comprimento (mm), L1 = Comprimento (2) (mm), I = Profundidade de encaixe (mm)

PDF: /images/pdf/capitulo1/01-22.pdf