

01.39 Reducer male/female with reinforce ring

PVC-U

Threaded

21 references

21 with CAD file

G	G1	I	Z	S	Weight (g)	Pack	REF.	3D
" 3/8	" 1/2	32	16	32	21	A 50	01021006024	sim
" 1/2	" 3/4	40	26	38	37	B 120	01021006003	sim
" 3/4	" 1/2	39	25	32	27	B 150	01021006005	sim
" 3/4	1 "	43	25	46	48	B 80	01021006027	sim
1 "	" 1/2	42	31	32	31	B 110	01021006006	sim
1 "	" 3/4	45	29	38	42	B 90	01021006007	sim
1 "	1" 1/4	52	29	55	73	B 40	01021006030	sim
1" 1/4	" 1/2	46	32	32	47	B 60	01021006008	sim
1" 1/4	" 3/4	50	34	38	56	B 50	01021006009	sim
1" 1/4	1 "	50	32	46	68	B 50	01021006010	sim
1" 1/4	1" 1/2	54	30	65	114	B 30	01021006033	sim
1" 1/2	" 1/2	48	32	32	50	B 50	01021006011	sim
1" 1/2	" 3/4	51	34	38	59	B 50	01021006012	sim
1" 1/2	1 "	52	32	46	70	B 50	01021006013	sim
1" 1/2	1" 1/4	51.5	30	55	77	B 35	01021006014	sim
1" 1/2	2 "	57	30	79	155	B 20	01021006036	sim
2 "	" 3/4	55	37	38	85	B 35	01021006015	sim
2 "	1 "	55	36	46	106	B 35	01021006016	sim
2 "	1" 1/4	58	37	55	109	B 35	01021006017	sim
2 "	1" 1/2	60	36	64	133	B 25	01021006018	sim
2" 1/2	2 "	37	61	79	180	B 20	01021006049	sim

Dimension key: G = Rosca (in), G1 = Rosca (2.ª saída) (in), I = Profundidade de encaixe (mm)

PDF: /images/pdf/capitulo1/01-39.pdf