

**01.39 Reducción macho/hembra con anilla de refuerzo**

PVC-U

Roscar

21 referencias

21 con archivo CAD

| G      | G1     | I    | Z  | S  | Peso (g) | Emb.  | REF.        | 3D  |
|--------|--------|------|----|----|----------|-------|-------------|-----|
| " 3/8  | " 1/2  | 32   | 16 | 32 | 21       | A 50  | 01021006024 | sim |
| " 1/2  | " 3/4  | 40   | 26 | 38 | 37       | B 120 | 01021006003 | sim |
| " 3/4  | " 1/2  | 39   | 25 | 32 | 27       | B 150 | 01021006005 | sim |
| " 3/4  | 1 "    | 43   | 25 | 46 | 48       | B 80  | 01021006027 | sim |
| 1 "    | " 1/2  | 42   | 31 | 32 | 31       | B 110 | 01021006006 | sim |
| 1 "    | " 3/4  | 45   | 29 | 38 | 42       | B 90  | 01021006007 | sim |
| 1 "    | 1" 1/4 | 52   | 29 | 55 | 73       | B 40  | 01021006030 | sim |
| 1" 1/4 | " 1/2  | 46   | 32 | 32 | 47       | B 60  | 01021006008 | sim |
| 1" 1/4 | " 3/4  | 50   | 34 | 38 | 56       | B 50  | 01021006009 | sim |
| 1" 1/4 | 1 "    | 50   | 32 | 46 | 68       | B 50  | 01021006010 | sim |
| 1" 1/4 | 1" 1/2 | 54   | 30 | 65 | 114      | B 30  | 01021006033 | sim |
| 1" 1/2 | " 1/2  | 48   | 32 | 32 | 50       | B 50  | 01021006011 | sim |
| 1" 1/2 | " 3/4  | 51   | 34 | 38 | 59       | B 50  | 01021006012 | sim |
| 1" 1/2 | 1 "    | 52   | 32 | 46 | 70       | B 50  | 01021006013 | sim |
| 1" 1/2 | 1" 1/4 | 51.5 | 30 | 55 | 77       | B 35  | 01021006014 | sim |
| 1" 1/2 | 2 "    | 57   | 30 | 79 | 155      | B 20  | 01021006036 | sim |
| 2 "    | " 3/4  | 55   | 37 | 38 | 85       | B 35  | 01021006015 | sim |
| 2 "    | 1 "    | 55   | 36 | 46 | 106      | B 35  | 01021006016 | sim |
| 2 "    | 1" 1/4 | 58   | 37 | 55 | 109      | B 35  | 01021006017 | sim |
| 2 "    | 1" 1/2 | 60   | 36 | 64 | 133      | B 25  | 01021006018 | sim |
| 2" 1/2 | 2 "    | 37   | 61 | 79 | 180      | B 20  | 01021006049 | sim |

Leyenda de cotas: G = Rosca (in), G1 = Rosca (2.ª saída) (in), I = Profundidade de encaixe (mm)

PDF: /images/pdf/capitulo1/01-39.pdf