

02.05 Coude à 90°

PVC-U	À coller / souder	19 références	19 avec fichier CAO
-------	-------------------	---------------	---------------------

d	D	I	Z	PN	Poids (g)	Cond.	RÉF.	3D
12	16	19	7	16	5	A 100	01051001012	sim
16	21	23	9	16	9	A 50	01051001016	sim
20	25	27	11	16	12	B 170	01051001020	sim
25	31	33	14	16	23	B 90	01051001025	sim
32	40	39	17	16	46	B 50	01051001032	sim
40	49	47	21	16	75	C 120	01051001040	sim
50	60	57	26	16	121	C 64	01051001050	sim
63	75.5	72	34	16	265	C 32	01051001063	sim
75	87.5	82	38	16	335	C 20	01051001075	sim
90	105	97	46	16	560	C 12	01051001090	sim
110	129	118	56	16	1060	D 16	01051001110	sim
125	145	135	66	16	1500	D 12	01051001125	sim
140	162	149	72	16	2000	D 8	01051001140	sim
160	185	167	81	16	2890	D 5	01051001160	sim
200	228	210	103	10	5000	D 2	01051001200	sim
225	255	233	114	10	6600	D 2	01051001225	sim
250	284	258	126	10	9300	E 1	01051001250	sim
315	356	332	167	10	18250	H 1	01051001315	sim
400	437	415	207	6	24880	J 1	01051001400	sim

Légende des cotes: d = Ø exterior do tubo (mm), D = Ø exterior do acessório (mm), I = Profundidade de encaixe (mm), PN = Pressão nominal (bar)

PDF: /images/pdf/capitulo2/02-05.pdf