

02.07 Coude à 45°

PVC-U

À coller / souder

19 références

19 avec fichier CAO

d	D	I	Z	PN	Poids (g)	Cond.	RÉF.	3D
12	16	16	4	16	4	A 150	01051067012	sim
16	21	18	4	16	7	A 60	01051067016	sim
20	25	21	5	16	11	B 200	01051067020	sim
25	31	25	6	16	18	B 100	01051067025	sim
32	40.5	30	8	16	40	B 60	01051067032	sim
40	49.5	36	10	16	65	C 150	01051067040	sim
50	61	43	12	16	116	C 80	01051067050	sim
63	75	53	15	16	195	C 40	01051067063	sim
75	87.5	61	17	16	255	C 24	01051067075	sim
90	106	72	21	16	484	C 14	01051067090	sim
110	129	86	25	16	815	D 20	01051067110	sim
125	145	96	27	16	1124	D 16	01051067125	sim
140	162	107	30	16	1514	D 10	01051067140	sim
160	185	121	34	16	2290	D 6	01051067160	sim
200	230	150	43,5	10	3962	D 2	01051067200	sim
225	255	167	48	10	5210	E 2	01051067225	sim
250	284	185	53	10	7110	E 1	01051067250	sim
315	356	235	70	10	13500	H 1	01051067315	sim
400	437	297	89	6	19000	J 1	01051067400	sim

Légende des cotes: d = Ø exterior do tubo (mm), D = Ø exterior do acessório (mm), I = Profundidade de encaixe (mm), PN = Pressão nominal (bar)

PDF: /images/pdf/capitulo2/02-07.pdf