

02.08 Socket

PVC-U

Solvent weld / fusion

19 references

19 with CAD file

d	D	I	Z	PN	Weight (g)	Pack	REF.	3D
12	16	27	3	16	4	A 150	01051005012	sim
16	21	31	3	16	6	A 100	01051005016	sim
20	26	35	3	16	9	B 200	01051005020	sim
25	31	41	3	16	15	B 120	01051005025	sim
32	40	47	3	16	29	B 70	01051005032	sim
40	48	55	3	16	42	C 180	01051005040	sim
50	59.5	65	3	16	75	C 120	01051005050	sim
63	75.5	79	3	16	145	C 57	01051005063	sim
75	90	94	4	16	246	C 36	01051005075	sim
90	106	107	4	16	376	C 18	01051005090	sim
110	129	131	9	16	625	C 12	01051005110	sim
125	145	145	6	16	820	D 24	01051005125	sim
140	162	162	8	16	1144	D 14	01051005140	sim
160	186.5	182	8	16	1770	D 10	01051005160	sim
200	230	222	8	10	3030	E 3	01051005200	sim
225	252	248	10	10	3300	E 2	01051005225	sim
250	280	274	11	10	4520	E 2	01051005250	sim
315	350	344	16	10	8400	D 1	01051005315	sim
400	432	430	16	6	11700	J 1	01051005400	sim

Dimension key: d = Ø exterior do tubo (mm), D = Ø exterior do acessório (mm), I = Profundidade de encaixe (mm), PN = Pressão nominal (bar)

PDF: /images/pdf/capitulo2/02-08.pdf