

02.09 Tapon hembra

PVC-U

Encolar / soldar

18 referencias

18 con archivo CAD

d	D	I	PN	Peso (g)	Emb.	REF.	3D
12	16	17	16	3	A 250	01051012012	sim
16	21	19	16	5	A 100	01051012016	sim
20	26	22	16	7	A 80	01051012020	sim
25	31	26	16	10	B 200	01051012025	sim
32	40	29	16	20	B 120	01051012032	sim
40	48	34.5	16	29	B 80	01051012040	sim
50	59.5	43	16	55	C 200	01051012050	sim
63	75.5	50	16	106	C 120	01051012063	sim
75	90	60	16	182	C 60	01051012075	sim
90	106	68	16	320	C 38	01051012090	sim
110	129	89	16	529	C 18	01051012110	sim
125	145	100	16	710	C 13	01051012125	sim
140	162	110	16	926	C 10	01051012140	sim
160	185	128	16	1495	C 6	01051012160	sim
200	231	160	10	2750	C 3	01051012200	sim
225	252	167	10	2600	C 2	01051012225	sim
250	280	185	10	3430	D 4	01051012250	sim
315	350	233	10	7170	D 2	01051012315	sim

Leyenda de cotas: d = Ø exterior do tubo (mm), D = Ø exterior do acessório (mm), I = Profundidade de encaixe (mm), PN = Pressão nominal (bar)

PDF: /images/pdf/capitulo2/02-09.pdf