

02.23 Bride libre

PVC-U

Bride

14 références

14 avec fichier CAO

d	A	B	K	I	Y	Furos	PN	Poids (g)	Cond.	RÉF.	3D
50	150	62	110	16	18	4	16	225	C 70	01051019050	sim
63	165	78	125	18	18	4	16	297	C 50	01051019063	sim
75	185	92	145-140	19	18	4	16	340	C 40	01051019075	sim
90	200	110	160-152	20	18	8	16	386	C 34	01051019090	sim
110	220	133	180	22	18	8	16	450	C 25	01051019110	sim
125	226	147	190	24	18	8	16	575	C 22	01051019125	sim
140/125	248	147	210	26	18	8	16	823	C 17	01051308140	sim
140	248	165	210	26	18	8	16	676	C 17	01051019140	sim
160	285	190	240	28	22	8	16	1034	C 10	01051019160	sim
200/225	340	232	295-286	30	22	8	10	1494	E 10	01051308200	sim
225	340	250	295	32	22	8	10	1200	E 10	01051019225	sim
250	395	278	350	36	22	12	10	2070	D 10	01051019250	sim
315	445	345	400	36	22	12	10	2150	Q 2	01051019315	sim
400	565	438	515	42	26	16	6	3980	R 1	01051019400	sim

Légende des cotes: d = Ø exterior do tubo (mm), I = Profundidade de encaixe (mm), Furos = N.º de furos (un), PN = Pressão nominal (bar)

PDF: /images/pdf/capitulo2/02-23.pdf