

02.41 Blind flange with grooves

PVC-U

Flanged

13 references

13 with CAD file

d	A	K	I	Y	Furos	PN	Weight (g)	Pack	REF.	3D
50	150	110	16	18	4	10	252	C 70	01051340050	sim
63	165	125	18	18	4	10	360	C 50	01051340063	sim
75	185	145	19	18	4	10	480	C 40	01051340075	sim
90	200	160	20	18	8	10	610	C 34	01051340090	sim
110	220	180	22	18	8	10	754	C 25	01051340110	sim
125	226	190	24	18	8	10	831	C 18	01051340125	sim
140	248	210	26	18	8	10	1060	C 17	01051340140	sim
160	285	240	28	22	8	10	1390	C 10	01051340160	sim
200	340	286	30	22	8	10	2500	E 10	01051340200	sim
225	340	295	32	22	8	10	2428	C 3	01051340225	sim
250	395	350	36	22	12	10	3630	S 5	01051340250	sim
315	445	400	36	22	12	10	4910	Q 2	01051340315	sim
400	565	515	42	26	16	6	9230	R 1	01051340400	sim

Dimension key: d = Ø exterior do tubo (mm), I = Profundidade de encaixe (mm), Furos = N.º de furos (un), PN = Pressão nominal (bar)

PDF: /images/pdf/capitulo2/02-41.pdf