

03.05 Coude à 90°

PVC-U

Raccordement: non défini

15 références

15 avec fichier CAO

d	G	D	I	I1	Z	Z1	Poids (g)	Cond.	RÉF.	3D
20	"1/2	30	27	27	11	11	26	B 120	01101002005	sim
25	"1/2	30	29	33	13	14	28	B 90	01101002006	sim
25	"3/4	37	33	33	15	14	48	B 70	01101002007	sim
32	"1/2	30	33	39	17	16.5	40	B 60	01101002050	sim
32	"3/4	37	35	39	17	16.5	48	B 50	01101002051	sim
32	1 "	45	38	38	20	20	74	B 40	01101002008	sim
40	1 "	45	44	47	24	20	85	B 35	01101002052	sim
40	1"1/4	53	49	47	26	20	109	B 25	01101002009	sim
50	1"1/4	53	55	57	32	25	125	B 15	01101002012	sim
50	1"1/2	64	60	57	37	25	203	B 15	01101002013	sim
63	1"1/2	76	68	72	45	34	263	B 10	01101002014	sim
63	2 "	76	73	72	46	34	308	B 10	01101002015	sim
75	2"1/2	87.5	82	82	52	38	335	B 6	01101002020	sim
90	3 "	105	97	97	67	46	620	C 12	01101002030	sim
110	4 "	132	121	121	82	58	1260	C 5	01101002040	sim

Légende des cotes: d = Ø exterior do tubo (mm), G = Rosca (in), D = Ø exterior do acessório (mm), I = Profundidade de encaixe (mm), I1 = Profundidade de encaixe (2) (mm)

PDF: /images/pdf/capitulo3/03-05.pdf