

04.10 Tapped valve (Teflon-VITON)

PVC-U

Threaded

11 references

11 with CAD file

G	DN	A	B	H	L	M	S	Z	L1	L2	Weight (g)	Pack	REF.	3D
"3/8	15	48	46	70	84	35	10	44	20	15	130	B 40	01611296038	sim
"1/2	15	48	46	70	84	35	10	44	20	15	130	B 40	01611296012	sim
"3/4	20	58.5	56	85	101	46	13	54	23.5	16	196	C 60	01611297034	sim
"3/4	25	68	71	105	112	54	18	66	23	16	354	C 40	01611296034	sim
1"	25	68	71	105	126	54	18	66	30	19	360	C 40	01611296100	sim
1"1/4	40	95	93	141	149	65	21	88	30.5	21	817	C 16	01611296114	sim
1"1/2	40	95	93	141	157	65	21	88	34.5	22	854	C 16	01611296150	sim
2"	50	115	107	164	190	74	23	102	44	26	1433	C 10	01611296200	sim
2"1/2	65	151	122	197	214	100	25	116	49	31	2530	C 4	01611296250	sim
3"	80	185	148	240	249	123	30	130	59	35	3860	C 3	01611296300	sim
4"	80	185	148	240	230	123	30	130	50	35	3800	C 3	01611296400	sim

Dimension key: G = Rosca (in), DN = Diâmetro nominal (mm), L = Comprimento (mm), L1 = Comprimento (2) (mm), L2 = Comprimento (3) (mm)

PDF: /images/pdf/capitulo4/04-10.pdf