

09.13 Reducing sockets male/female

PP-R

Solvent weld / fusion

14 references

14 with CAD file

d	d1	D	Z	I	Weight (g)	Pack	REF.	3D
25	20	30	37	21	12	B 150	02052006005	sim
32	20	30	43	27	16	B 100	02052006006	sim
32	25	36	43	25	20	B 90	02052006007	sim
40	20	30	24.5	42.5	19	B 130	02052006015	sim
40	25	36	26	44	22	B 120	02052006016	sim
40	32	43	28	46	29	C 300	02052006017	sim
50	20	30	27	48	32	C 170	02052006020	sim
50	25	36	28.5	49.5	34	C 220	02052006021	sim
50	32	43	30.5	51.5	38	C 180	02052006022	sim
50	40	54	33	54	51	C 170	02052006023	sim
63	25	36	33	60	59	C 150	02052006027	sim
63	32	43	33	60	64	C 150	02052006028	sim
63	40	54	34	61	66	C 120	02052006029	sim
63	50	64	37	64	84	C 90	02052006030	sim

Dimension key: d = Ø exterior do tubo (mm), d1 = Ø exterior do tubo (2.ª saída) (mm), D = Ø exterior do acessório (mm), I = Profundidade de encaixe (mm)

PDF: /images/pdf/capitulo9/09-13.pdf