

19.09 Coudes à 90° femelle

Matière: non défini Fileté 17 références

d	d1	A	B	C	D	E	F	G	H	Poids (g)	Cond.	RÉF.	3D
20	" 1/2	91	68	39	22	22	12	7	3.5	68	-	20412002005	-
20	" 3/4	91	67	39	22	22	12	7	3.5	65	-	20412002006	-
25	" 1/2	104	73	41	27	26	13	10	4	84	-	20412002009	-
25	" 3/4	104	74	41	27	26	13	10	4	79	-	20412002010	-
25	1"	92	74	41	27	26	13	10	4	83	-	20412002011	-
32	" 3/4	121	79	52	34	33	19	12	5	122	-	20412002013	-
32	1"	121	74	52	34	33	19	12	5	117	75	20412002015	-
40	1" 1/4	137	97	61	41	41	23	13	6	200	75	20412002020	-
40	1" 1/2	137	96	61	41	41	23	13	6	239	75	20412002021	-
50	1" 1/2	154	111	68	51	51	31	13	6.5	325	55	20412002025	-
50	2"	156	112	68	51	51	31	13	6.5	350	55	20412002026	-
63	2"	191	134	83	64	64	39	22	7	505	30	20412002030	-
63	2" 1/2	191	137	83	64	64	39	22	7	600	30	20412002031	-
75	2" 1/2	217	172	107	76	77	40	23	8	790	15	20412002060	-
75	3"	220	174	107	76	77	40	23	8	920	15	20412002061	-
90	3"	265	170	131	94	91	57	31	8	1190	10	20412002065	-
110	4"	337	233	166	112	112	57	36	9	2240	6	20412002070	-

Légende des cotes: d = Ø exterior do tubo (mm), d1 = Ø exterior do tubo (2.ª saída) (in), D = Ø exterior do acessório (mm), G = Rosca (mm)

PDF: /images/pdf/capitulo19a/19-09.pdf