

19.12 Coudes à 90° mâle

Matière: non défini Fileté 19 références

d	d1	A	B	C	D	E	F	G	H	I	Poids (g)	Cond.	RÉF.	3D
16	" 1/2	75	56	39	35	17	17	12	12	3	37	-	20412085003	-
16	" 3/4	75	57	39	35	17	17	12	12	3	37	-	20412085004	-
20	" 1/2	85	61	46	39	22	22	12	7	3.5	52	-	20412085005	-
20	" 3/4	89	33	46	39	22	22	12	7	3.5	50	-	20412085006	-
25	" 1/2	90	69	52	41	27	27	13	10	4	75	-	20412085009	-
25	" 3/4	91	69	52	41	27	27	13	10	4	76	-	20412085010	-
25	1"	93	78	52	41	27	27	13	10	4	79	-	20412085011	-
32	" 3/4	121	84	64	52	34	33	19	12	5	122	-	20412085014	-
32	1"	112	84	64	52	34	33	19	12	5	119	-	20412085015	-
40	1" 1/4	136	92	78	61	41	41	23	13	6	210	90	20412085020	-
40	1" 1/2	137	92	78	61	41	41	23	13	6	190	90	20412085021	-
50	1" 1/2	153	111	92	68	51	52	31	13	6.5	320	60	20412085025	-
50	2"	153	115	92	68	51	52	31	13	6.5	355	60	20412085026	-
63	2 "	191	133	109	83	64	65	39	22	7	525	30	20412085030	-
63	2" 1/2	191	134	109	83	64	65	39	22	7	520	30	20412085031	-
75	2" 1/2	219	172	132	107	76	78	40	23	8	730	15	20412085060	-
75	3"	218	172	132	107	76	78	40	23	8	835	15	20412085061	-
90	3"	265	172	151	131	94	92	57	31	8	1180	10	20412085065	-
110	4"	336	221	175	166	112	113	57	36	9	2040	6	20412085070	-

Légende des cotes: d = Ø exterior do tubo (mm), d1 = Ø exterior do tubo (2.ª saída) (in), D = Ø exterior do acessório (mm), G = Rosca (mm), I = Profundidade de encaixe (mm)

PDF: /images/pdf/capitulo19a/19.12-13.pdf