

19.14 Tés à 90° mâle

Matière: non défini

Fileté

22 références

d	d1	A	B	C	D	E	F	G	H	Poids (g)	Cond.	RÉF.	3D
16	" 1/2	101	55	39	17	17	12	12	3	63	-	20412086003	-
16	" 3/4	101	58	39	17	17	12	12	3	63	-	20412086004	-
20	" 1/2	117	64	46	22	22	12	7	3.5	104	-	20412086005	-
20	" 3/4	117	66	46	22	22	12	7	3.5	104	-	20412086006	-
20	1"	117	68	46	22	22	12	7	3.5	113	-	20412086007	-
25	" 1/2	130	72	52	27	26	13	10	4	129	-	20412086009	-
25	" 3/4	130	72	52	27	26	13	10	4	132	-	20412086010	-
25	1"	130	74	52	27	26	13	10	4	133	-	20412086011	-
32	" 1/2	152	78	64	34	33	19	12	5	196	100	20412086013	-
32	" 3/4	152	79	64	34	33	19	12	5	206	100	20412086014	-
32	1"	152	83	64	34	33	19	12	5	204	85	20412086015	-
40	1"	178	96	78	41	42	23	13	6	367	50	20412086019	-
40	1" 1/4	178	101	78	41	42	23	13	6	368	50	20412086020	-
40	1" 1/2	178	111	78	41	42	23	13	6	373	50	20412086021	-
50	1" 1/2	199	115	92	51	52	31	13	6.5	528	30	20412086025	-
50	2"	199	115	92	51	52	31	13	6.5	538	30	20412086026	-
63	2"	248	138	109	64	65	39	22	7	717	20	20412086030	-
75	2"	276	171	132	76	78	40	23	8	1348	10	20412086059	-
75	2" 1/2	276	171	132	76	78	40	23	8	1280	10	20412086060	-
75	3"	276	171	132	76	78	40	23	8	1416	10	20412086061	-
90	3"	344	196	151	94	92	57	31	8	2250	6	20412086065	-
110	4"	480	220	175	112	113	57	36	9	3680	4	20412086070	-

Légende des cotes: d = Ø exterior do tubo (mm), d1 = Ø exterior do tubo (2.ª saída) (in), D = Ø exterior do acessório (mm), G = Rosca (mm)

PDF: /images/pdf/capitulo19a/19.14-15.pdf