

19.31 Té à 90°

Matière: non défini

Raccord rapide

10 références

| d   | A   | L   | Z   | Z1 | I   | Poids (g) | Cond. | RÉF.        | 3D |
|-----|-----|-----|-----|----|-----|-----------|-------|-------------|----|
| 16  | 47  | 54  | 26  | 13 | 134 | 127       | 30    | 20402003016 | -  |
| 20  | 47  | 54  | 26  | 13 | 134 | 115       | 30    | 20402003020 | -  |
| 25  | 54  | 56  | 34  | 17 | 146 | 165       | 20    | 20402003025 | -  |
| 32  | 63  | 61  | 36  | 18 | 158 | 250       | 12    | 20402003032 | -  |
| 40  | 80  | 74  | 46  | 23 | 194 | 441       | 5     | 20402003040 | -  |
| 50  | 94  | 85  | 56  | 28 | 226 | 726       | 8     | 20402003050 | -  |
| 63  | 116 | 95  | 58  | 29 | 248 | 1300      | -     | 20402003063 | -  |
| 75  | 121 | 134 | 96  | 48 | 364 | 1900      | -     | 20402003075 | -  |
| 90  | 146 | 155 | 102 | 51 | 416 | 2850      | -     | 20402003090 | -  |
| 110 | 176 | 176 | 116 | 58 | 468 | 4750      | -     | 20402003110 | -  |

Légende des cotes: d = Ø exterior do tubo (mm), L = Comprimento (mm), I = Profundidade de encaixe (mm)

PDF: /images/pdf/capitulo19b/19-31.pdf